

SHACMAN

L3000

LORRY TRUCK



Transport type		Standard load transport		
Logistics type		Daily use and food/agricultural and sideline products		
Distance(km)		≤200km		
Road type		Urban / National Road		
Drive		4×2		
Max weight(t)		12~18		
Crusing speed/Max speed(km/h)		90	90	90
Loaded speed(km/h)		55~65	45~65	55~65
Vehicle model		SX11858K571	SX11888K501	SX11858J501C
Engine		WP6.240E32	WP6.245E50	ISDe210 30
Emission standard		Euro II	EuroV	Euro III
Displacement		6.23L	6.75L	6.7L
Rated Output		186kW	180kW	155kW
Max. torque		/	900N·m	800N·m
Transmission		8JS85TE-C	8JS85TE-C	8JS85TE-C
Clutch		395	395	395
Frame		870×250(7+4)	870×250(7+4)	870×250(7+4)
Front axle		4.8T (Disc brake)	4.8T (Disc brake)	4.8T (Disc brake)
Rear axle		10T single reduction 4.625	10T single reduction 4.625	10T single reduction 4.625
Tire		10.00R20	10.00R20	10.00R20
Front Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel		Diesel	Diesel	Diesel
Capacity of the fuel tank		200L	200L	200L
Battery		135Ah	135Ah	135Ah
Trunk(L×W×H)		7750×2450×600	6750×2450×600	6750×2450×600
Wheelbase		5700	5000	5000
After the suspension		2600	2300	2300
Max.gradeability(%)		45	45	45
Cab	Type	L3000 Cab		
	Equipments	◆ Electric air conditioning ◆ Electric window lifter ◆ LED daytime running light ◆ Central locking (double remote control) ◆ Front fixed rear hydraulic shock absorber		
Vehicle	Optional	● Deflector ● Air main seat ● Electric flip		