

SHACMAN

L3000

DUMP TRUCK



Transport type		Urban construction wastes transport			
Logistics type		Construction wastes, etc			
Distance(km)		≤50		≤100	
Road type		Urban / suburban roads		Urban road / suburban road / National Road	
Drive		4×2	4×2	4×2	4×2
Max weight(t)		≤18	≤18	≤30	≤30
Max speed(km/h)		100	100	105	105
Loaded speed(km/h)		60~70	65~70	65~75	55~75
Vehicle model		SX31858F401	SX31888F401	SX3185MJ381	SX3188MJ381
Engine		WP6.180E32	WP6.180E50	WP6.210E32	WP6.220E50
Emission standard		EuroII	EuroV	EuroII	EuroV
Displacement		6.23L	6.75L	6.23L	6.75L
Rated Output		132kW	132kW	155kW	162kW
Max. torque		/	680N·m	750N·m	850N·m
Transmission		8JS85TE-C+QD40J	8JS85TE-C+QD40J	8JS85TE-C+QD40J	8JS85TE-C+QD40J
Clutch		395	395	395	395
Frame		870×270(7+4)	870×270(7+4)	850×300(8+5)	850×300(8+5)
Front axle		4.8T(Drum brake)	4.8T(Drum brake)	7.5T(Drum brake)	7.5T(Drum brake)
Rear axle		11.5T MAN single reduction axle 5.286	11.5T MAN single reduction axle 5.286	16T MAN double reduction5.262	16T MAN double reduction5.262
Tire		10.00R20	10.00R20	12.00R20	12.00R20
Front Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs	Multi leaf springs
Rear Suspension		Multi leaf springs	Multi leaf springs	Multi leaf springs	Multi leaf springs
Fuel		Diesel	Diesel	Diesel	Diesel
Capacity of the fuel tank		200L	200L	300L	300L
Battery		135Ah	135Ah	165Ah	165Ah
Trunk(L×W×H)		4200×2300×900	4200×2300×900	4000×2300×1000	4000×2300×1000
Wheelbase		4000	4000	3800	3800
Max.gradeability(%)		38	38	27	27
Cab	Type	L3000 (Upgraded)cab			
	Equipments	◆ Electric air conditioning ◆ Electric window lifter ◆ LED daytime running light ◆ Central locking (double remote control) ◆ Front fixed rearhydraulic shock absorber ◆ Fleetguard ◆ Hydraulic main seat with third seat ◆ Manual flip		◆ Electric air conditioning ◆ Electric window lifter ◆ Central locking (double remote control) ◆ Hydraulic shock absorber ◆ Fleetguard ◆ Hydraulic main seat ◆ Manual flip	